

FoundryGeneral® Metal Cleaner CM --

Section 1. Supplier Information



FoundryGeneral® c/o General Chemical Corp.

12336 Emerson Drive
www.foundrychem.com
Brighton, MI 48116
(248) 587-5600

Emergency Telephone: 1-800-424-9300

Section 2. Hazardous Ingredients

<u>Hazardous Component(s)</u>	<u>CAS #</u>	<u>PEL TWA</u>	<u>PEL Ceiling</u>	<u>TLV TWA</u>	<u>TLV STEL</u>	<u>MFG Limits</u>	<u>WGT %</u>
N-Methyl-2-pyrrolidone	872-50-4	N/E	N/E	N/E	N/E	N/E	35 - 50
Solvent naphtha, heavy arom.	64742-94-5	5 mg/m3	N/E	5 mg/m3*	10 mg/m	N/E	35 - 50
Monoethanolamine	141-43-5	3 ppm	N/E	3 ppm	6 ppm	N/E	< 20
Surfactant	Proprietary	N/E	N/E	N/E	N/E	N/E	1 - 10

N/A = Not Applicable; N/E = Not Established; * = Mists; # = Skin; ' = Respirable Dust; " = Total Dust; ^ = Vapor; ** = Fumes; C = Ceiling Limit

All components of this product are listed on the Toxic Substances Control Act (TSCA) Inventory and the Canadian Domestic Substances List (DSL), or are exempt from the listing.

Section 3. Hazards Identification

Signs of Symptoms of Exposure:

Section 6. Accidental Release Measures

If material is spilled, eliminate all ignition sources. Keep people away. Recover free product. Add sand, earth or other suitable absorbent to spill area; place in closed containers for disposal. Ventilate confined spaces. Keep product out of sewers and watercourses by diking or impounding. Advise authorities if product has entered or may enter sewers, watercourses, or extensive land areas. Continue to observe precautions for volatile, combustible vapors from absorbed material.

CERCLA (Superfund) Reportable Quantity (in lbs) The naphthalene in this material is covered by CERCLA's petroleum exclusion (40 CFR 300.5), therefore, releases are not reportable under EPA-CERCLA.

FoundryGeneral® Metal Cleaner CM --

Section 7. Handling and Storage

Handling: Avoid contact with skin and eyes; wash thoroughly after handling. Avoid breathing vapor; use with adequate ventilation.

Storage: Store in a dry location at room temperature. Keep container closed and maintain all original markings and labels. Keep this container and vapors from this container away from heat, sparks, flame, and other ignition sources.

Other: CAUTION! Do not use cutting or welding torches on containers, even when empty. Containers, even those that have been emptied, will retain product residue and vapors. Do not reuse container without recycling or reconditioning. Handle empty containers as if they were full.

Section 8. Exposure Controls and Personal Protection

Respiratory Protection: Use NIOSH / MSHA approved respirator where high vapor or mist concentrations are present.

Local Exhaust: Special ventilation is suggested at points where vapors can be expected to escape to the workplace air.

Mechanical Exhaust: Mechanical ventilation should be sufficient to maintain exposure levels below exposure limits.

Protective Gloves: Butyl rubber and FEP Teflon provide the best resistance.

Eye Protection: Safety glasses with side shields. Do NOT wear contact lenses. Chemical goggles and/or faceshield should be worn where splashing is possible.

Other Protection: Eye wash and safety shower should be readily available. Wear a chemical resistant apron and boots where splashing is possible.

Hygienic Practices: Protective equipment and clothing should be selected, used and maintained according to applicable standards and regulations. For further information, contact the clothing or equipment manufacturer. Do not eat, drink, or smoke while using this product. Wash hands prior to eating, drinking, smoking, or using restrooms. Cleanse skin thoroughly after contact, before breaks and meals, and at the end of the work shift.

Section 11. Toxicological Information

N-methyl-2-pyrrolidone [CASRN 000872-50-4]

ACUTE TOXICITY

Oral LD50 (rat) = 4,990 mg/kg (moderately toxic) Eye Irritation (rabbit) - markedly irritating
Oral LD50 (mouse) = 5,270 mg/kg (slightly toxic) Skin irritation (rabbit) - markedly irritating
Inhalation LC50 (rat) > 5.1 mg/L, 4 hr (moderately toxic) Inhalation safety screen (rat), 8 hr - slightly irritating (No deaths)

Acute Overexposure Effects: Contact with the liquid can result in irritation. Skin contact should be avoided. Prolonged skin contact may result in redness and dermatitis. NMP is moderately toxic by all routes of exposure; however, due to its low vapor pressure, dermal exposure represents the primary hazard in most settings. Contact with the liquid results in moderate eye irritation and may cause temporary corneal clouding. Skin contact results in mild irritation; prolonged skin contact may cause redness and dermatitis. Inhalation of the vapors of NMP may result in respiratory irritation. Accidental ingestion of the liquid causes gastric disturbances and may result in nausea and vomiting.

FoundryGeneral® Metal Cleaner CM --

Reproductive / Development Effects: In animal studies NMP was embryotoxic by the oral, dermal and intraperitoneal routes, but only after repeated high doses that approached the LD50 or were maternally toxic. Embryotoxicity without maternal toxicity was observed at a high concentration in one rat inhalation study, but not in others. Testicular effects in rats were noted after repeated, high-dose oral and inhalation exposures. NMP was not carcinogenic in rats receiving lifetime exposures via inhalation (100 ppm) or the diet. NMP was not fetotoxic or teratogenic in rats exposed to NMP vapors up to 0.36 mg/l during gestation (Fund. and Appl. Tox. 9:222-235, 1987). NMP has been reported to cause aneuploidy in saccharomyces, but is not mutagenic in the Ames test (Env. and Molec. Mut. 11(1) 31-40, 1988). [1-13,12,15-062001], [11,24-13,12,15-110200]

Solvent naphtha (petroleum), heavy aromatic [CASRN 064742-94-5]

ACUTE TOXICITY

Oral LD50 (rat) = 10 ml/kg Eye irritation (rabbit): slightly irritating.
Dermal LD50 (rat) > 4.0 ml/kg Dermal irritation (rabbit, 4 hrs.): slightly irritating.
Inhalation LC50 (rat) > 710 ppm, 4 hr

Other Testing: Repeated inhalation exposure of rats to a related material at irritating concentrations caused decreased white blood cell counts. [18,7-18,0,B,F,A-060500]

Monoethanolamine [CASRN 000141-43-5]

ACUTE TOXICITY

Oral LD50 (rat) = 1.00 - 2.00 g/kg Eye irritation (rabbit): Draize; 80.0 - 110 ; extreme irritation
Dermal LD50 (rabbit) > 1.6 g/kg Skin irritation (rabbit): Draize; 6.5- 8.0 ; corrosive

Prolonged and repeated ingestion of monoethanolamine has caused kidney and liver damage in laboratory animals. [7,20-12,4,0-091200], [3-12-092600] & [20,2-12-061900]

Surfactant

ACUTE TOXICITY

Oral LD50 (rat, ♀) = 2.83 ml/kg Eye Irritation (rabbit) = 0.005 ml (severe corneal injury)
Oral LD50 (rat, ♂) = 2.33 ml/kg Eye Irritation (rabbit) = 0.5 ml; 15% dilution in water (severe corneal injury)
Dermal LD50 (rabbit, 24 hr) = 2.83 ml/kg Dermal Irritation (rabbit) - 24 hr. uncovered (minimal capillary injection)
Inhalation (rat, 8 hr, rm. tmp.) - mortality 0/6 Inhalation (rat, 8 hr, 170 °C) - mortality 0/6 [20,2-19,13,15,J,18-102300]

Section 12. Ecological Information

N-methyl-2-pyrrolidone [CASRN 000872-50-4]

ECOTOXICITY

96 hr LC50 (golden orfe) = 4,000 mg/l, static 24 hr EC/LC50 (daphnia magna) > 1000 mg/l
72 hr EC/LC50 (algal) > 500 mg/l IC50 (bacteria) > 9000 mg/l

Fate: Abiotic Degradability: Photolysis Half-Life 5.2 hrs. Biotic Degradability: BOD 92% (14 day).

Theo. BOD (Modified MITI Test) 73 % (28 day)

Elimination (method not specified) > 90 %, Readily Biodegradable

Chemical Oxygen Demand: 1600 mg/l, Readily Biodegradable

Biological Oxygen Demand, 5 day: 1100 mg/l, Readily Biodegradable

Octanol/Water partition coefficient (log POW): -0.46 [11,24-13,12,15-110200], [1-13,12,15-062001]

FoundryGeneral® Metal Cleaner CM --

Monoethanolamine [CASRN 000141-43-5]

ECOTOXICITY

48 hr - LC50 (daphnia) = 33-93 mg/L 96 hr - LC50 (fathead minnow) = 125-206 mg/l
IC50 (bacteria) > 700 mg/l
IC50 Activated Sludge Respiration Inhibition Test (OECD Test No. 209) is >1000 mg/L.

FATE

BOD Day 5 - 52-60% Theoretical Oxygen Demand (ThOD): 1.31 mg/mg, calc.
BOD Day 10 - 73-75% Octanol/Water Partition Coefficient : -1.31, measured
BOD Day 20 - 90-100 % Henry's law constant (H): 2.45E-7 atm m3/mole (estimated)
Log Koc: 0.70 (estimated)
CO2 Evolution test (Modified Sturm test, OECD Test 301 B) after 28 days: 97%. Modified OECD
Screening test (OECD Test 301 E) after 28 days: 94%.
Manometric Respirometry test (OECD Test 301 F) after 28 days: > 70%
[7,20-12,4,0-091200], [3-12-092600] & [20,2-12-061900]
Surfactant

ECOTOXICITY

48 hr - LC50 (daphnia magna) = 21.4 mg/L 96 hr - LC50 (fathead minnow) = 4.8 - 7.7 mg/L
96 hr - LC50 (fathead minnow) = 6.6 mg/L IC50 (bacteria) > 5000 mg/L

ENVIRONMENTAL FATE

BOD 5 3-18 % Closed Bottle BOD (% Oxygen cons.) = 16%
BOD 10 32-36 % Chemical Oxygen Demand (COD) - 2.23 mg/mg, measured
BOD 20 42-51% Chemical Oxygen Demand (COD) - 2.09 mg/mg, calc
DOC 7 61% STURM (% Carbon dioxide evolved) = 52.4-59%
DOC 14 66% Theoretical Oxygen Demand (ThOD) - 2.09 mg/mg, measured
DOC 21 70%
DOC 28 72%

Appropriate treatment of effluents will reduce levels of nonylphenol ethoxylate (NPE) residues to concentrations that should pose no harm to the environment, including protection for weak estrogen-mimetic activity observed for some degradation intermediates. [20,2-19,13,15,J,18-102300]

Section 13. Disposal Considerations

Waste Disposal Methods (Federal, State, Local):

In accordance with all federal, state and local requirements.

RCRA Hazardous Waste Number: N/A

Section 14. Transport Information

Hazardous Material Description:

(Proper shipping name, hazard class, hazard ID#, packing group)

Domestic ground non-bulk: UN2491, ETHANOLAMINE SOLUTION, 8, PG III

Domestic ground bulk: UN2491, ETHANOLAMINE SOLUTION, 8, PG III

International: UN2491, ETHANOLAMINE SOLUTION, 8, PG III

FoundryGeneral® Metal Cleaner CM --

Section 15. Regulatory Information

SARA 313 Information This product contains the following chemical(s) above de minimis concentrations and may be subject to reporting under section 313:

n-Methyl-2-pyrrolidone, CAS# 872-50-4, 35-50 %

1,2,4-Trimethylbenzene (in solvent naphtha), CAS# 95-63-6, < 5 %

Naphthalene (in solvent naphtha), CAS# 91-20-3, <3.5 %

Section 16. Other Information

This MSDS contains revisions in the following sections: New product

Prepared by: General Chemical

Revised by:

The development of this Material Safety Data Sheet (MSDS) relies upon information provided to us by each of our raw material suppliers. This MSDS will be updated as changes occur to their MSDS(s).

We believe the recommendations and technical information contained herein to be accurate. However, they are given without warranty or guarantee, expressed or implied, and we assume no responsibility for losses or damage, direct or indirect, as a result of their use.