

FoundryGeneral® No Bake Release 4414 --

Section 1. Supplier Information



FoundryGeneral® c/o General Chemical Corp.

12336 Emerson Drive
www.foundrychem.com
Brighton, MI 48116
(248) 587-5600

Emergency Telephone: 1-800-424-9300

Section 2. Hazardous Ingredients

<u>Hazardous Component(s)</u>	<u>CAS #</u>	<u>PEL TWA</u>	<u>PEL Ceiling</u>	<u>TLV TWA</u>	<u>TLV STEL</u>	<u>MFG Limits</u>	<u>WGT %</u>
Hydrocarbon naphtha	64742-89-8	N/E	N/E	300 ppm	N/E	N/E	> 80
Aluminum	7429-90-5	5 mg/m3	15 mg/m	10 mg/m3	N/E	N/E	< 5
Mineral spirits	8052-41-3	500 ppm	N/E	100 ppm	N/E	N/E	< 3

N/A = Not Applicable; N/E = Not Established; * = Mists; # = Skin; ' = Respirable Dust; " = Total Dust; ^ = Vapor; ** = Fumes; C = Ceiling Limit

All components of this product are listed on the Toxic Substances Control Act (TSCA) Inventory and the Canadian Domestic Substances List (DSL), or are exempt from the listing.

Section 3. Hazards Identification

Primary Routes of Entry

Inhalation: YES
Skin: YES
Ingestion: YES

Hazardous Materials Information System (HMIS) Ratings

Health: 1
Fire: 3
Reactivity: 0
0 = Minimal
1 = Slight
2 = Moderate
3 = Serious
4 = Severe
* = Chronic Hazard

Signs of Symptoms of Exposure:

INHALATION: High vapor or mist concentrations may produce nose, throat, and respiratory irritation and may cause central nervous system (CNS) depression.

SKIN: Material is mildly irritating to the skin. Prolonged or repeated contact may cause defatting and drying of the skin, resulting in irritation and dermatitis.

EYES: Minimally irritating to the eyes. High vapor concentrations may be irritating.

INGESTION: Ingestion of this product may result in vomiting. Aspiration (breathing) of vomitus into the lungs must be avoided, as even small quantities may result in aspiration pneumonitis.

Chemical Listed as Potential Carcinogens:

NTP: NO

IARC: NO

OSHA: NO

Target Organs: Eyes, skin, respiratory system, and CNS.

FoundryGeneral® No Bake Release 4414 --

Section 4. Emergency And First Aid Procedures

INHALATION: If adverse effects such as dizziness, nausea, or irritation are noted, move person to fresh air. If not breathing, give artificial respiration. Get medical attention!

SKIN: Immediately wash skin with large amounts of soap and water. Remove contaminated clothing and shoes; wash before reuse. Get medical attention if irritation persists after washing.

EYES: Flush eyes immediately with water for at least 15 minutes. If irritation persists, call a physician.

INGESTION: DO NOT INDUCE VOMITING! Contact a physician immediately!

Section 5. Fire Fighting Measures

Flash Point: 65 ° F

Method Used: Tagliabue Closed Cup

Flammable Limits in Air % by Volume: LEL: 1.3 UEL: 10.2 ; for petroleum distillate

Extinguisher Media: Dry chemical, carbon dioxide, or foam. Use water to cool exposed containers.

Special Fire Fighting Procedures: Firefighters should wear a self-contained breathing apparatus with a full facepiece operated in pressure demand or other positive pressure mode, and protective clothing.

Unusual Fire And Explosion Hazards: Product is flammable and may be ignited by heat, sparks, static electricity, or open flame.

Section 6. Accidental Release Measures

If material is spilled, eliminate all ignition sources. Keep people away. Recover free product. Add sand, earth or other suitable absorbent to spill area; place in closed containers for disposal. Ventilate confined spaces. Keep product out of sewers and watercourses by diking or impounding. Advise authorities if product has entered or may enter sewers, watercourses, or extensive land areas. Continue to observe precautions for volatile, combustible vapors from absorbed material.

CERCLA (Superfund) Reportable Quantity (in lbs None).

Section 7. Handling and Storage

Handling: Avoid contact with skin and eyes; wash thoroughly after handling. Avoid breathing vapor; use with adequate ventilation.

Storage: Store in a dry location at room temperature. Keep container closed and maintain all original markings and labels. Keep this container and vapors from this container away from heat, sparks, flame, and other ignition sources. Do not store near oxidizable material.

Other: Do not store above 100 °F. CAUTION! Do not use cutting or welding torches on containers, even when empty. Containers, even those that have been emptied, will retain product residue and vapors. Do not reuse container without recycling or reconditioning. Handle empty containers as if they were full.

Section 8. Exposure Controls and Personal Protection

Respiratory Protection: Use NIOSH / MSHA approved respirator where high vapor or mist concentrations are present.

Local Exhaust: None normally required. Local exhaust may be needed under special circumstances such as poorly ventilated areas, evaporation from large surfaces, spraying, heating, etc.

FoundryGeneral® No Bake Release 4414 --

Mechanical Exhaust: Mechanical ventilation should be sufficient to maintain exposure levels below exposure limits.

Protective Gloves: Wear chemical resistant gloves.

Eye Protection: Safety glasses with side shields. Do NOT wear contact lenses. Chemical goggles and/or faceshield should be worn where splashing is possible.

Other Protection: Eye wash and safety shower should be readily available. Wear a chemical resistant apron and boots where splashing is possible.

Hygienic Practices: Avoid contact with skin and avoid breathing vapors or mist. Do not eat, drink, or smoke while using this product. Wash up prior to eating, drinking, or using the restroom.

Section 9. Physical and Chemical Properties

Boiling Point:	> 240 ° F	Degree of water solubility:
Specific Gravity (H ₂ O=1):	0.7 - 0.9	Negligible = Less than 0.1%
Vapor Pressure (mm Hg):	~ 18	Slight = 0.1% - 1%
Vapor Density (air=1)	> 3.5	Moderate = 1% - 10%
Solubility in Water:	Negligible.	Appreciable = More than 10%
Reactivity in Water:	None.	Complete = 100%
Weight per Gallon (lb/gal):	6.0 - 7.0 lbs/gal	
% Volatile by Volume:	92-94	
% Solid by Weight:	6-8	
Appearance and Odor:	Silver gray liquid with a naphtha odor.	
Theoretical VOC: (>0.1 mm Hg @ 20 ° C)	6.0 - 6.1 lbs/gal	
Analytical VOC : (EPA method 24)	6.0 - 6.1 lbs/gal	
pH:	N/A ; product is solvent based.	

Section 10. Stability and Reactivity

Stability: Stable. Hazard Polymerization: Will not occur!

Conditions to Avoid: FLAMMABLE! Keep from heat, sparks, or open flame.

Incompatibility (Materials to Avoid): Strong oxidizing agents.

Hazardous Decomposition Products: Aluminum fume, silicon oxides, and oxides of carbon.

Section 11. Toxicological Information

Mineral Spirits [CASRN 008052-41-3]

ACUTE TOXICITY Oral LD50 (rat) > 5 g/kg Dermal LD50 (rat) > 2 g/kg
Inhalation LC50 (rat), 4 hr > 5500 mg/kg
Eye Irritation, Draize (rabbit) moderate irritation (500 mg /24 hr) [20,8-18,18-120197]

FoundryGeneral® No Bake Release 4414 --

Section 12. Ecological Information

Section 13. Disposal Considerations

Waste Disposal Methods (Federal, State, Local):

In accordance with all federal, state and local requirements.

RCRA Hazardous Waste Number: D001

Section 14. Transport Information

Hazardous Material Description:

(Proper shipping name, hazard class, hazard ID#, packing group)

Domestic ground non-bulk: UN1268, PETROLEUM DISTILLATES, N.O.S., 3, PG II

Domestic ground bulk: UN1268, PETROLEUM DISTILLATES, N.O.S., 3, PG II

International: UN1268, PETROLEUM DISTILLATES, N.O.S., 3, PG II

Section 15. Regulatory Information

SARA 313 Information

'This product contains the following chemical(s) above deminis concentrations and may be subject to reporting under section 313:

Aluminum (fume or dust), CAS# 7429-90-5, < 5%.

Section 16. Other Information

This MSDS contains revisions in the following sections: New product

Prepared by: General Chemical

Revised by:

The development of this Material Safety Data Sheet (MSDS) relies upon information provided to us by each of our raw material suppliers. This MSDS will be updated as changes occur to their MSDS(s).

We believe the recommendations and technical information contained herein to be accurate. However, they are given without warranty or guarantee, expressed or implied, and we assume no responsibility for losses or damage, direct or indirect, as a result of their use.